

DUAL WALL PIPE

LOW-HEAD TRANSMISSION, SANITITE™, BLUE SEAL®, SURE-LOK® F477, ECOFIRST® & HI-Q®

CHARACTERISTICS

PRODUCT	DESCRIPTION	DIAMETER RANGE	LENGTH	CONNECTION	SPECIFICATIONS/ PERFORMANCE
DUAL WALL					
LOW-HEAD TRANSMISSION	Annular Corrugation with Smooth Interior manufactured with HDB resins. 24"-60" (600-1500mm) diameters have a reinforced bell-and-spigot including a bell tolerance device covered with a protective wrap. The gasket is reinforced with a closed cell structural foam core.	18"-60" (450-1500mm)	18"-30" (450-750mm) 13' or 20' (3.9 or 6m) 36"-60" (900-1500mm) 13' or 20.5' (3.9 or 6.24m)	Bell-and-spigot with rubber gasket meeting ASTM F477 providing testable watertight performance.	18"- 60" (450-1500mm) meets a modified ASTM F894.
SANITITE	Annular Corrugation with Smooth Interior manufactured with HDB resins. 24"-60" (600-1500mm) diameters have a reinforced bell-and-spigot including a bell tolerance device covered with a protective wrap. The gasket is reinforced with a closed cell structural foam core.	18"-60" (450-1500mm)	18"-30" (450-750mm) 13' or 20' (3.9 or 6m) 36"-60" (900-1500mm) 13' or 20.5' (3.9 or 6.24m)	Bell-and-spigot with rubber gasket meeting ASTM F477 providing testable watertight performance.	18"- 60" (450-1500mm) meets a modified ASTM F894.
BLUE SEAL	Annular Corrugation with Smooth Interior 24"-60" (600-1500mm) diameters have a reinforced bell-and-spigot including a bell tolerance device covered with a protective wrap. The gasket is reinforced with a closed cell structural foam core.	12"-60" (300-1500mm)	12"-30" (300-750mm) 20' (6m) 36-60" (900-1500mm) 20.5' (6.24m)	Bell-and-spigot with rubber gasket meeting ASTM F477 providing testable watertight performance.	12"- 60" (300-1500mm) meets AASHTO M294, Type S.
SURE-LOK F477	Annular Corrugation with Smooth Interior.	4"-60" (100-1500mm)	4"-30" (100-750mm) 20' (6m) 36"-60" (900-1500mm) 20.5' (6.24m)	Bell-and-spigot with rubber gasket meeting ASTM F477 providing testable soil- and silt-tight performance.	4"-10" (100-250mm) meets AASHTO M252, Type S. 12"-60" (300-1500mm) meets AASHTO M294, Type S.
ECOFIRST	Annular Corrugation with Smooth Interior made from recycled polyethylene.	4"-60" (100-1500mm)	4"-30" (100-750mm) 20' (6m) 12"-30" (300-750mm) Plain End 30' (9m) 12"-30" (300-750mm) Bell-and-Spigot 9.4' (2.8m) 36"-60" (900-1500mm) Bell-and-Spigot 20.5' (6.24m)	Bell-and-spigot with rubber gasket meeting ASTM F477 providing soil- and silt-tight performance. Plain end External snap or split band couplers depending on diameter.	4"-8" (100-200mm) meets requirements of AASHTO M252, Type S, except raw material requirements. 12"-30" (300-750mm) meets requirements of AASHTO M294, Type S, except raw material requirements.
HI-Q	Annular Corrugation with Smooth Interior.	4"-30" (100-750mm)	20' (6m)	External snap or split band couplers depending on diameter.	4"-10" (100-250mm) meets AASHTO M252, Type S. 12"-30" (300-750mm) meets AASHTO M294, Type S.